

## CEILING WHITE

### Description

Colormaker Industries Ceiling White is a premium quality water-based vinyl paint, which is exceptionally easy to apply and has minimal roller spatter. Its excellent opacity and extremely low gloss make it an ideal coating for hiding surface imperfections, or when an ultra-flat and even finish is desired.

### Areas of Use

Colormaker Industries Ceiling White is specifically intended for application over domestic interior set plaster or paper-faced plasterboard ceilings. Other interior wall surfaces not subject to normal contact can also be considered suitable. Ceiling White is not recommended for any surfaces requiring washability, or in wet areas such as bathrooms or kitchens.

### Features

- Water based vinyl coating
- Excellent opacity
- Ultra-flat finish
- Hides minor surface imperfections
- Easy to apply
- Low roller spatter

### Typical Properties

<b>Colour:</b>	White. (May be tinted to light pastel colours)
<b>Finish:</b>	Flat
<b>Theoretical Spreading Rate:</b>	12-14m <sup>2</sup> /L
<b>Touch Dry Time:</b>	20-30 minutes at 25°C, 50% relative humidity
<b>Recoat Time:</b>	2-4 hours at 25°C, 50% relative humidity

### Packaging

Available in 15L and 10L plastic re-sealable pails, and 4L and 2L lined steel cans

### Precautions

- Do not apply if the temperature falls below 10°C, or rises above 35°C, or is likely to fall outside these limits during drying, or when humidity is very high.
- The product is supplied ready for use. DO NOT THIN with water as this will influence both application characteristics and opacity.

## Preparation

### Prior to painting

All surfaces to be thoroughly cleaned and free of scale, dust, dirt, oil and grease. If oil or grease is evident, wash with a suitable detergent/degreaser and then rinse with fresh water before application. Thoroughly remove kalsomine with warm water, detergent and a stiff brush. If mould is present, treat the surface with an anti-mould solution, and then rinse with fresh water before application.

Previously painted surfaces should be scraped free of all loose and flaking paint using a paint scraper or wire brush. Any painted or glossy surfaces should be lightly abraded with suitable sand-paper until slightly rough to touch.

Fill any cracks, holes, or joins with a suitable filler and sand back until smooth and flush to the surface.

### Priming

Colormaker Industries Ceiling White can be applied without priming over properly prepared pre-painted surfaces that are in sound condition.

For new unpainted set plaster and paper-faced plasterboard, ColorPrep 3 in 1 Acrylic Primer-Sealer-Undercoat is recommended.

Spot prime any holes, cracks or joins that have been suitably filled with ColorPrep 3 in 1 Acrylic Primer-Sealer-Undercoat.

Follow the directions of use for all primers, and ensure the primer has completely cured before coating with Ceiling White.

### Application

- Stir thoroughly prior to use with a broad, flat paddle using an up and down scooping action for at least 5 minutes.
- Apply a minimum of two even coats, covering smaller rather than large areas at any time. Allow suitable recoat time between coats
- Brush and roller application is typically recommended, but spray application may be used.

**Brush:** Apply liberally and lay off with tip of the brush to cut in edges only.

**Roller:** An 8-10mm nap roller is recommended for general use, however a 20mm nap is suggested for use on rough or textured surfaces.

**Spray:** Use a 4-5 mm tip preferably with an airless spray system.

### Coverage

12-14m<sup>2</sup>/L dependant on the porosity and texture of the surface.

### Clean-up

Reseal containers immediately after use.

Clean all equipment while paint is still wet with water, keeping away from drains and open watercourses.

### Storage and Shelf Life

Store in a cool, dry place in sealed containers. Shelf life before opening is 24 months.

Once opened and resealed, ideally use the remaining contents within 6 months.

### Health, Safety & Environment

This material is non-toxic and non-flammable however the contents should not be inhaled or ingested.

If swallowed immediately rinse mouth and then drink plenty of water. Seek medical advice.

Wash any paint splashes on the skin with clean water. If irritation occurs seek medical advice.

If the event of eye contact immediately irrigate with plenty of fresh water for at least 15 minutes. Hold eyelids open. In all cases of eye contamination, it is a sensible precaution to seek medical advice.

In the event of a spill, contain the spread of paint to prevent contamination of drains and waterways. Clean up spills with absorbent materials such as soil, sand, or vermiculite, and then collect and seal in properly labelled containers for disposal. Wash area with fresh water. SDS is available upon request.

**VER1407**

### Product Disclaimer

The technical advice and/or application advice given in this publication represents the present state of our knowledge, and is believed to be reliable. Buyers and intended users of all Colormaker Industries products should read the TDS carefully and then conduct their own assessment to confirm the suitability of the product, including in conjunction with other products, and the types of surfaces to, and the manner in which, the product will be applied. Colormaker Industries offers no warranty of performance based on the above information, either expressed or implied.

## COLORMAKER INDUSTRIES

44 Orchard Rd, Brookvale NSW 2100

Phone: +61 2 9939 7977

Email: [info@colormaker.com.au](mailto:info@colormaker.com.au)

[www.colormaker.com.au](http://www.colormaker.com.au)