

GRASS COATING

Description

Colormaker Grass coating is an eco friendly, water based, bio-degradable coating suitable for line markings and field areas on grass without harming the grass itself.

Area of Use

Line marking on Grass / lawn

Features

- Ecofriendly water based grass coating
- Quick and easy to apply
- Bio-degradable

Typical properties

Colour: White and Black

Finish : Matt

Theoretical Spreading rate: 12-14 m²/L but can vary with grass surface and intensity of required marking

Touch Dry time: 20-30 minutes at 25°C, 50% relative humidity

Recoat Time: Normally one coat is sufficient but in case second coat is needed then recoat after 2 hours at 25°C, 50% relative humidity

Precautions

- Do not apply when temperature is below 10 °C or likely to drop during the drying
- Not designed for use on any other surfaces other than grass.
- Ensure Grass coating is applied evenly and avoid thick applications. It is important that the grass still receives sunlight through the coating to ensure it will continue to grow.

Surface preparation

Trim grass to an even length. Ensure grass is dry prior to application.

Application

Stir thoroughly the paint prior to use with a broad, flat paddle using an up and down scooping action for at least 5 minutes.

The paint may be thinned with 2-3 parts water making it cost-effective option for all field marking projects and for ease of application.

Apply by brush, roller or spray.

To remove the Grass coating wait for the grass to grow and then cut the lawn. This will cut off the painted area.

Coverage: 12-14 m²/L but can vary with grass surface and intensity of required marking

Clean-up

Reseal containers immediately after use.

Clean all equipment while paint is still wet with water, keeping away from drains and open watercourses.

Storage and Shelf Life

Store in a cool, dry place in sealed containers. Shelf life before opening is 24 months.

Once opened and resealed, ideally use the remaining contents within 6 months.

Health, Safety & Environment

This material is non-toxic and non-flammable however the contents should not be inhaled or ingested.

If swallowed immediately rinse mouth and then drink plenty of water. Seek medical advice.

Wash any paint splashes on the skin with clean water. If irritation occurs seek medical advice.

If the event of eye contact immediately irrigate with plenty of fresh water for at least 15 minutes.

Hold eyelids open. In all cases of eye contamination, it is a sensible precaution to seek medical advice.

In the event of a spill, contain the spread of paint to prevent contamination of drains and waterways. Clean up spills with absorbent materials such as soil, sand, or vermiculite, and then collect and seal in properly labelled containers for disposal. Wash area with fresh water.

SDS is available upon request.

VER1602

Product Disclaimer

The technical advice and/or application advice given in this publication represents the present state of our knowledge, and is believed to be reliable. Buyers and intended users of all Colormaker Industries products should read the TDS carefully and then conduct their own assessment to confirm the suitability of the product, including in conjunction with other products, and the types of surfaces to, and the manner in which, the product will be applied. Colormaker Industries offers no warranty of performance based on the above information, either expressed or implied.